

Eka SC

Sodium Chlorate

Eka SC is sodium chlorate; a white to off-white crystalline material in its dry form.

CAS number
7775-09-9

Molecular weight
106.45

Molecular formula
NaClO₃

Sodium chlorate characteristics

NaClO ₃	≥ 99.6 wt%
NaCl	≤ 0.1 wt%
H ₂ O	≤ 0.2 wt%
Cr	≤ 8 ppm
Fe	≤ 5 ppm
Insolubles	≤ 20 ppm
Appearance	White to off-white crystal
Density, poured	1400-1650 kg/m ³
Density, tapped	1450-1800 kg/m ³

Applications

Eka SC (sodium chlorate) is essential to environmentally compatible paper pulp bleaching. It is the functional ingredient in the generation of chlorine dioxide, which, in turn, is the main component in ECF (Elemental Chlorine-Free) bleaching. Up to 95 percent of all sodium chlorate produced worldwide is consumed by the pulp industry. Its second most common use is by the chemical industry where it is used as a precursor in the production of sodium and ammonium perchlorate and sodium chlorite. Sodium chlorate and sodium chlorite are the common precursors to chlorine dioxide, which is used in many water treatment applications. Other common industrial applications for sodium chlorate include as an oxidant in the mining industry for the extraction of uranium and vanadium; in the automotive industry as a surface treatment for metals; it is also used in the Printed Circuit Board industry for the control and replenishment of the cupric chloride etchant. This versatile chemical is utilized in many devices that require an oxygen source (e.g. breathing apparatus).

Packaging and transport

Depending on the customer set-up, Eka SC is shipped in bulk tank, drums or in supersacks. Eka SC is classified as hazardous material and consequently transportation and packaging design must adhere to the all applicable transportation regulations. Transportation may take place by road, railway, air or sea. Each mode of transport demands specific regulations with special requirements regarding packaging, vehicle and documentation.

Proper shipping name	Sodium Chlorate
UN number	1495
Transportation hazard class	5.1
Packaging group	II

Safety and handling

Please refer to the current SDS (Safety Data Sheet) for preventive protection and first aid response. Eka SC is classified as dangerous goods. It is a strong oxidizing agent and is very soluble in water. Crystal sodium chlorate is stable at temperatures up to 250°C (482°F). Above this temperature chlorate decomposes and oxygen is liberated. Be aware that sodium chlorate in liquid form is a hazard as well. Sodium chlorate solution is a clear odorless liquid that may become invisible when it dries on any organic material like cloth, leather, paper or wood. All that is required is a spark, minor friction or heat, to ignite. Sodium chlorate in its pure form is not flammable; however, due to the fact it releases oxygen during decomposition, it will act as an extreme combustion accelerant in the presence of flammable materials. Additional information on the handling of Eka SC is available in the Sodium Chlorate Product Information Manual that can be obtained from your Nouryon representative.

Mandatory protective equipment

Because sodium chlorate should never come in contact with organic materials like cloth and leather; make sure, as a minimum, all personnel handling Eka SC are provided with, and required to wear, the following items:

Measure 1	A protective suit (preferred anti-flammable treated) made of vinyl, neoprene, or PVC
Measure 2	A pair of vinyl or neoprene boots
Measure 3	Protective goggles that fit snugly over the eyes
Measure 4	Vinyl or neoprene gloves
Measure 5	A hard-hat with a full-face shield

Additional information

Production at all Nouryon sites is in accordance with certified management systems. To receive a copy of the current certificate(s) contact your Nouryon representative. Nouryon representatives will be pleased to discuss in detail the safe handling, application and benefits of Eka SC. To arrange your personal interview, please contact your Nouryon account representative, email bleaching_experts@nouryon.com or call one of the numbers below.

All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Nouryon, however, makes no warranty as to accuracy and/or sufficiency of such information and/or suggestions, as to the product's merchantability or fitness for any particular purpose, or that any suggested use will not infringe any patent. Nouryon does not accept any liability whatsoever arising out of the use of or reliance on this information, or out of the use or the performance of the product. Nothing contained herein shall be construed as granting or extending any license under any patent. Customer must determine for himself, by preliminary tests or otherwise, the suitability of this product for his purposes. The information contained herein supersedes all previously issued information on the subject matter covered. The customer may forward, distribute, and/or photocopy this document only if unaltered and complete, including all of its headers and footers, and should refrain from any unauthorized use. Don't copy this document to a website.

Contact Us

Bohus

+46 31 58 70 00

bleaching_experts@nouryon.com

Marietta

+1 770 578 0858

bleaching_experts@nouryon.com

Jundiai

+55 11 4589 4800

bleaching_experts@nouryon.com

Shanghai

+86 21 2289 1000

bleaching_experts@nouryon.com

The Nouryon logo consists of a stylized orange 'N' followed by the word 'ouryon' in a lowercase, sans-serif font, all in orange.