

# Witbreak DRM-9510

## Polyacrylate

Witbreak® DRM-9510 demulsifier is a polyacrylate intermediate used in oilfield production primarily as a Water Dropper and Dryer, interchangeably, and sometimes as an Interface Control Agent for a wide range of API crudes globally, including low-temperature applications.

### Specifications

Appearance	Amber liquid at 25°C
Moisture	≤ 0.50 %
pH	5.5-7.0 (5% in 1:3 IPA/H2O)
Relative Solubility Number	7.6-8.8

### Characteristics

Appearance	Liquid amber at 25°C
Brookfield viscosity, 77°F	1160 cps
Density	8.2 Lbs/Gal at 25°C
Flash point	61 C
Odor	Solvent
pH	6 (5% in 3:1 IPA/H2O)
Pour point	-17.8 °C
Relative Solubility Number	7.9
Water content	≤ 0.5 %
Solubility: 10% in Aromatic 150	Soluble
Solubility: 10% in Isopropyl Alcohol	Soluble
Solubility: 10% in Kerosene	Insoluble
Solubility: 10% in Water	Dispersible
Solubility: 10% in Xylene	Soluble
Solubility: 50% in Aromatic 150	Soluble
Solubility: 50% in Isopropyl Alcohol	Soluble
Solubility: 50% in Kerosene	Insoluble
Solubility: 50% in Water	Insoluble
Solubility: 50% in Xylene	Soluble

#### Notes:

Typical Data are based on our own measurements or derived from the literature. They do not constitute part of the delivery specification.

## **Applications**

Witbreak® DRM-9510 is a polymerized polyol. Witbreak® DRM-9510 works by effectively neutralizing the strength of the natural emulsifying agent, allowing the finely dispersed water droplets to coalesce. As the tiny water droplets merge into progressively larger and heavier drops, the water settles and the oil rapidly rises to the top. The result is a sharp, well-defined oil/water interface and bright, clean and marketable oil.

## **Additional information**

Witbreak® DRM-9510 is one part of Nouryon's line of high performance emulsion-breaker chemicals. Witbreak® DRM-9510 has been specially developed to provide fast resolution of stable emulsions in which water is the internal phase and oil is the external phase. Witbreak® DRM-9510 displays exceptional water dropping, desalting and oil brightening characteristics. Its unique chemistry enables this concentrate to be used as is or formulated with other bases to achieve very specific applications for a wide variety of crudes, including low gravity emulsions. Witbreak® DRM-9510 may be used in typical continuous treatment systems as well as downhole and in batch applications, optimizing the oil treatment process.

All information concerning this product and/or suggestions for handling and use contained herein are offered in good faith and are believed to be reliable. Nouryon, however, makes no warranty as to accuracy and/or sufficiency of such information and/or suggestions, as to the product's merchantability or fitness for any particular purpose, or that any suggested use will not infringe any patent. Nouryon does not accept any liability whatsoever arising out of the use of or reliance on this information, or out of the use or the performance of the product. Nothing contained herein shall be construed as granting or extending any license under any patent. Customer must determine for himself, by preliminary tests or otherwise, the suitability of this product for his purposes. The information contained herein supersedes all previously issued information on the subject matter covered. The customer may forward, distribute, and/or photocopy this document only if unaltered and complete, including all of its headers and footers, and should refrain from any unauthorized use. Don't copy this document to a website.

Witbreak® is a registered trademark in many countries. For more information, please visit our website at [www.nouryon.com](http://www.nouryon.com).

The Nouryon logo consists of the word "Nouryon" in a bold, blue, sans-serif font. The letter "N" is slightly taller than the other letters, and there is a small gap between the "N" and the rest of the word.

Nouryon