



Rediset® LQ-1200

Compaction aid for hot and warm mixes. Lower odor and storage stable in hot binder. Allows a reduction in mixing and paving temperatures while providing active and passive adhesion.

Benefits and features

- Active adhesion**
 Bitumen treated with Rediset LQ-1200 has the ability to coat damp aggregate which ensures good coverage even at lower mix temperatures
- Heat stability**
 Performance is maintained after long storage in hot bitumen
- Improved workability and compaction**
 Mixes remain workable to lower temperatures and are easier to compact, which enables cool weather paving, longer haul distances and faster paving operations
- Moisture resistance**
 Treated bitumen has exceptional long-term adhesion enabling mixes meet specifications for moisture resistance. Additional adhesion promoter is not required
- Lower odor**
 Contains less volatile ingredients which reduces odor at higher mixing temperatures

Dosage

Hot and warm mix*	0.3-0.8%	basis binder
Compaction aid for hot mix	0.3-0.5%	basis binder
Adhesion promoter	0.3-0.5%	basis binder

*Dosage dependent on magnitude of temperature reduction and type of mixes

Specification

Amine value, mg KOH/g	784	SM 5.005
Water, %	max 1	VE 5.022

Physical properties

Appearance at 25°C (77°F)	liquid			
Flash point, °C	230 (446°F)			
Pour point, °C	<-20 (-4°F)			

	10	20	30	40	°C
	50	68	86	104	°F
Density, g/cc	0.981	0.975	0.969	0.962	
Density, lbs/U.S. gal	8.14	8.19	8.09	8.03	
Viscosity, mPa.s (cP)	650	471	230	135	

Storage and handling

Rediset LQ-1200 may be stored in carbon steel tanks. Bulk storage should be maintained at 15-30°C (60-86°F). Rediset LQ-1200 contains amines and is corrosive to skin and eyes. Protective gloves and safety goggles must be used when handling this product. For further information consult the Safety Data Sheet.

Physical properties are typical data based on our own measurements or derived from the literature. They do not constitute part of the delivery specification.

Packaging information

Rediset LQ-1200 is available in bulk delivery, in tight-head steel drums of 190 kg (419 lb) net weight or in one-way totes (IBCs) of 950 kg (2093 lb).

Notes

For more information see the Technical Bulletin: Rediset LQ.

Contact us directly for detailed product information and sample request
website | nouryon.com/markets/asphalt
email | asphalt@nouryon.com

Nouryon

Nouryon is a global, specialty chemicals leader. Markets and consumers worldwide rely on our essential solutions to manufacture everyday products, such as personal care, cleaning goods, paints and coatings, agriculture and food, pharmaceuticals, and building products. Furthermore, the dedication of more than 7,900 employees with a shared commitment to our customers, business growth, safety, sustainability and innovation has resulted in a consistently strong financial performance. We operate in over 80 countries around the world with a portfolio of industry-leading brands. Visit our website and follow us @Nouryon and on LinkedIn.

All information concerning our products and/or all suggestions for handling and use contained herein (including formulation and toxicity information) are offered in good faith and are believed to be reliable. However, Nouryon makes no warranty express or implied (i) as to the accuracy or sufficiency of such information and/or suggestions, (ii) as to any product's merchantability or fitness for a particular use or (iii) that any suggested use (including use in any formulation) will not infringe any patent. Nothing contained herein shall be construed as granting or extending any license under any patent. The user must determine for itself by preliminary tests or otherwise the suitability of any product and of any information contained herein (including but not limited to formulation and toxicity information) for the user's purpose. The safety of any formulations described herein has not been established. The suitability and safety of a formulation should be confirmed in all respects by the user prior to use. The information contained herein supersedes all previously issued bulletins on the subject matter covered.

Products mentioned are trademarks of Nouryon and registered in many countries.

nouryon.com