

Wetfix[®] 312

Liquid adhesion promoter for hot and warm mix. Adhesion promoter for cold and warm mix based on cut-back bitumen. Adhesion promoter and coating aid for foamed bitumen cold mix.

Benefits and features

- Value for money**
 Wetfix 312 is a concentrated product with consequent low dosage and low treatment costs
- Heat stability**
 The performance is maintained after storage in hot bitumen
- Low volatility**
 The product does not contain solvents and has low volatility at hot mix temperatures
- Combined systems**
 Treated bitumen has the ability to coat damp or wet aggregates, which ensures good coverage in applications like patch mix and cold mix techniques with foamed bitumen

Storage and handling

Wetfix 312 may be stored in carbon steel tanks. Bulk storage should be maintained at 10-40°C (50-105°F). Avoid heating above 65°C (150°F). Wetfix 312 contains amines and may cause severe irritation or burns to skin and eyes. Protective gloves and safety goggles must be worn when handling this product.

For further information consult the Safety Data Sheet.

Packaging information

Wetfix 312 is available in bulk shipments, in tight head steel drums of 400 lbs (181 kg) net weight, or in one-way totes (IBCs) of 2000 lbs (907 kg) net weight.

Dosage

Hot and warm mix	0.2-0.5%	basis binder
Patch mix	0.5-1.0%	basis binder

Specification

Amine value, mg KOH/g	370-410	SMA CL002
Water, %	max 1	SMA CL007

Physical properties

Appearance at 25°C (77°F)	liquid			
Flash point, °C	>200 (>392°F)			
Pour point, °C	<0 (<32°F)			

	10	20	30	40	°C
	50	68	86	104	°F
Density, g/cc	0.97	0.96	0.96	0.95	
Density, lbs/U.S. gal	8.08	8.00	7.97	7.92	
Viscosity, mPa.s (cP)	2250	1500	800	370	

Physical properties are typical data based on our own measurements or derived from the literature. They do not constitute part of the delivery specification.

Notes

For regulatory reasons this product is not available in Canada.

Contact us directly for detailed product information and sample request
website | nouryon.com/markets/asphalt
email | asphalt@nouryon.com

Nouryon

Nouryon is a global, specialty chemicals leader. Markets and consumers worldwide rely on our essential solutions to manufacture everyday products, such as personal care, cleaning goods, paints and coatings, agriculture and food, pharmaceuticals, and building products. Furthermore, the dedication of more than 7,900 employees with a shared commitment to our customers, business growth, safety, sustainability and innovation has resulted in a consistently strong financial performance. We operate in over 80 countries around the world with a portfolio of industry-leading brands. Visit our website and follow us @Nouryon and on LinkedIn.

All information concerning our products and/or all suggestions for handling and use contained herein (including formulation and toxicity information) are offered in good faith and are believed to be reliable. However, Nouryon makes no warranty express or implied (i) as to the accuracy or sufficiency of such information and/or suggestions, (ii) as to any product's merchantability or fitness for a particular use or (iii) that any suggested use (including use in any formulation) will not infringe any patent. Nothing contained herein shall be construed as granting or extending any license under any patent. The user must determine for itself by preliminary tests or otherwise the suitability of any product and of any information contained herein (including but not limited to formulation and toxicity information) for the user's purpose. The safety of any formulations described herein has not been established. The suitability and safety of a formulation should be confirmed in all respects by the user prior to use. The information contained herein supersedes all previously issued bulletins on the subject matter covered.

Products mentioned are trademarks of Nouryon and registered in many countries.

nouryon.com