

Product Specification

Carbon Disulphide

Chemical Name: Carbon Disulphide

Molecular Formula: CS₂

 Molecular Mass:
 76,1 g/mol

 CAS-No.:
 75-15-0

 EC-No.:
 200-843-6

Properties

Vapour Pressure (20 °C): 0,4 bar Refractive Index (20 °C): 1,627

Solubility (20 °C)

 CS_2 in Water: 2,1 g/l Water in CS_2 : 0,1 g/l Boiling Point (1 bar): 46,3 °C

Specification

Appearance: colourless, clear liquid

CS₂ Content min. 99,99% (calculated by difference from water free CS₂)

Boiling Range (1 bar): min. 98% at 46,0 – 46,4 °C

Density (20 °C): 1,262 – 1,266 kg/l Residue on Evaporation: max. 20 mg/kg

Hydrogen Sulphide (H_2S): Lead-Acetate-Test negative (\cong max. 3 mg/kg)

Iron: max. 1 mg/kg
Benzene: max. 30 mg/kg

Analytical methods are available on request.

Major Applications

Carbon Disulphide is a raw material for a large variety of chemical products. It is used in the manufacture of xanthates, which are intermediates for the production of regenerated cellulose products like viscose rayon, cellophane, cellulose sponges, etc. It is also used as a reaction agent for the production of rubber vulcanisation accelerators, fungicides and soil sterilisers. Carbon Disulphide is an effective solvent for oils, waxes, sulphur and many organic compounds.

Storage

Cool and padded with nitrogen or water. Requirements regarding storage tank design are available on request.

Packing and Transport

Carbon Disulphide is delivered in:

• Rail tank cars

ISO Tank Containers

· Road tankers

Hazard Identification No.: 336 UN-No.: 1131

Safety advice

Carbon Disulphide is highly inflammable and toxic and is classified as a hazardous substance. We therefore refer to our Material Safety Data Sheet (MSDS).

The information presented herein is true and accurate to the best of our knowledge, but without any guarantee unless explicitly given. Since the conditions of use are beyond our control we disclaim any liability including for patent infringement, incurred in connection with the use of this product, data and suggestions.

Carbosulf Chem. Werke GmbH Geestemünder Str. 26 50735 Cologne Germany T +49-221-7496-101 F +49-221-7496-190

https://sulfurderivatives.nouryon.com/